



MODEL	CAPACITY	DIM A	DIM B	WEIGHT
LB6-R1N19	525 LBS	4.22 [107mm]	3.03 [77mm]	14.64 LBS
LB6-R2N19	525 LBS	4.22 [107mm]	3.03 [77mm]	14.61 LBS
LB6-R3N19	525 LBS	4.41 [112mm]	3.22 [82mm]	14.81 LBS
LB6-R4N19	525 LBS	4.63 [117mm]	3.44 [87mm]	15.10 LBS
LB6-R5N19	525 LBS	5.06 [129mm]	3.88 [98mm]	15.70 LBS
LB6-R6N19	525 LBS	5.50 [140mm]	4.31 [110mm]	16.31 LBS
LB6-R7N19	525 LBS	4.25 [108mm]	1.50 [38mm]	16.92 LBS
LB6-R8N19	525 LBS	4.69 [119mm]	1.94 [49mm]	17.53 LBS
LB6-R9N19	525 LBS	4.69 [119mm]	1.94 [49mm]	17.50 LBS
LB6-R1S19	525 LBS	4.22 [107mm]	3.03 [77mm]	20.84 LBS
LB6-R2S19	525 LBS	4.22 [107mm]	3.03 [77mm]	20.60 LBS

L - LOFT
 B - BLOCK
 # - SHEAVE DIAMETER
 -
 R - UPRIGHT MOUNTING (TYPICAL)
 # - NUMBER OF GROOVES
 N - SHEAVE MATERIAL (N=NYLATRON, S=STEEL)
 # - ROPE SIZE

- NOTES:
- MAXIMUM RATED CAPACITY :
 - MAY EXCEED CAPACITY OF THE ROPE.
 - USE ROPE MANUFACTURER'S RATING AND SAFETY FACTOR TO DETERMINE LOAD LIMIT.
 - WHEN PROPERLY INSTALLED, MAINTAINED AND OPERATED.
 - IS BASED ON CABLES WRAPPED 90 DEGREES AROUND THE SHEAVE.
 - MOUNTING HARDWARE MUST BE DISTRIBUTED EVENLY.
 - MINIMUM OF 4 ATTACHMENT POINTS.
 - CONTACT FACTORY FOR NON-STANDARD REQUIREMENTS.

DRAWINGS FOR PRODUCTION APPROVAL. MANUFACTURE WILL NOT BEGUN UNTIL APPROVED DRAWING IS RETURNED TO THERN INC.		COMPANY NAME PRINT NAME	DATE
SIGNATURE		DATE	
DESCRIPTION 6" LOFT BLOCK			
MODEL	WEIGHT	TREAT	FINISH
TOLERANCES UNLESS OTHERWISE SPECIFIED FRACTIONAL ± .005 DECIMAL ± .005 DO NOT SCALE DRAWING	THIS PRINT IS THE PROPERTY OF THERN, INC. AND MUST NOT BE REPRODUCED EITHER IN FULL OR IN PART WITHOUT WRITTEN APPROVAL BY THERN, INC.	SCALE 1:2	DATE 8/28/2015
RETURN TO: THERN INC. P.O. BOX 947 WINDOM, MN 55085 PHONE: 1-855-454-2886 FAX: 1-855-454-2822		DRAWING NO. D4463	SHEET OF