



MODEL	CAPACITY	DIM A	DIM B	WEIGHT
LB8-R1N25	875 LBS	4.22 [107mm]	3.03 [77mm]	18.66 LBS
LB8-R2N25	875 LBS	4.22 [107mm]	3.03 [77mm]	18.58 LBS
LB8-R3N25	875 LBS	4.63 [117mm]	3.44 [87mm]	19.43 LBS
LB8-R4N25	875 LBS	5.06 [129mm]	3.88 [98mm]	20.38 LBS
LB8-R5N25	875 LBS	5.50 [140mm]	4.31 [110mm]	21.34 LBS
LB8-R6N25	875 LBS	4.25 [108mm]	1.50 [38mm]	22.30 LBS
LB8-R7N25	875 LBS	4.69 [119mm]	1.94 [49mm]	23.26 LBS
LB8-R8N25	875 LBS	5.13 [130mm]	2.38 [60mm]	24.27 LBS
LB8-R9N25	875 LBS	5.56 [142mm]	2.81 [71mm]	25.24 LBS
LB8-R1S25	875 LBS	4.22 [107mm]	3.03 [77mm]	29.95 LBS
LB8-R2S25	875 LBS	4.22 [107mm]	3.03 [77mm]	29.41 LBS
LB8-R3S25	875 LBS	4.63 [117mm]	3.44 [87mm]	26.22 LBS
LB8-R4S25	875 LBS	5.06 [129mm]	3.88 [98mm]	27.98 LBS
LB8-R5S25	875 LBS	5.50 [140mm]	4.31 [110mm]	29.75 LBS
LB8-R6S25	875 LBS	4.25 [108mm]	1.50 [38mm]	31.53 LBS
LB8-R7S25	875 LBS	4.69 [119mm]	1.94 [49mm]	33.30 LBS
LB8-R8S25	875 LBS	5.13 [130mm]	2.38 [60mm]	35.11 LBS
LB8-R9S25	875 LBS	5.56 [142mm]	2.81 [71mm]	36.90 LBS

L - LOFT
 B - BLOCK
 # - SHEAVE DIAMETER
 -
 R - UPRIGHT MOUNTING (TYPICAL)
 # - NUMBER OF GROOVES
 N - SHEAVE MATERIAL (N=NYLATRON, S=STEEL)
 # - ROPE SIZE

- NOTES:
1. MAXIMUM RATED CAPACITY :
 - MAY EXCEED CAPACITY OF THE ROPE.
 - USE ROPE MANUFACTURER'S RATING AND SAFETY FACTOR TO DETERMINE LOAD LIMIT.
 - WHEN PROPERLY INSTALLED, MAINTAINED AND OPERATED.
 - IS BASED ON CABLES WRAPPED 90 DEGREES AROUND THE SHEAVE.
 2. MOUNTING HARDWARE MUST BE DISTRIBUTED EVENLY.
 - MINIMUM OF 4 ATTACHMENT POINTS.
 3. CONTACT FACTORY FOR NON-STANDARD REQUIREMENTS.

DRAWINGS FOR PRODUCTION APPROVAL. MANUFACTURE WILL NOT BEGIN UNTIL APPROVED DRAWING IS RETURNED TO THERN INC.		COMPANY NAME PRINT NAME	SIGNATURE	DATE
DIMENSIONAL DRAWING				
8" LOFT BLOCK		RETURN TO: 275 HOLLISTON PARK ROAD P.O. BOX 247 WINDEN, NH 03091 PHONE 603-450-0386 FAX 603-450-0392		
TOLERANCES UNLESS OTHERWISE SPECIFIED: FRACTIONS DO NOT SCALE DRAWING		DATE JCA	NTS 9/28/2015	D4469