



| MODEL | CAPACITY | DIM A | DIM B | WEIGHT |
|---------------|----------|--------------|--------------|------------|
| HB16-D6N25DP | 2500 LBS | 2.44 [62mm] | 5.34 [136mm] | 98.66 LBS |
| HB16-D8N25DP | 2500 LBS | 3.31 [84mm] | 6.21 [158mm] | 105.95 LBS |
| HB16-D10N25DP | 2500 LBS | 4.19 [107mm] | 7.09 [180mm] | 113.27 LBS |
| HB16-D6S25DP | 2500 LBS | 2.44 [62mm] | 5.34 [136mm] | 130.51 LBS |
| HB16-D8S25DP | 2500 LBS | 3.31 [84mm] | 6.21 [158mm] | 142.97 LBS |
| HB16-D10S25DP | 2500 LBS | 4.19 [107mm] | 7.09 [180mm] | 155.47 LBS |
| HB16-D6N38DP | 2500 LBS | 3.75 [95mm] | 6.65 [169mm] | 107.57 LBS |
| HB16-D8N38DP | 2500 LBS | 4.88 [124mm] | 7.77 [198mm] | 115.28 LBS |
| HB16-D6S38DP | 2500 LBS | 3.75 [95mm] | 6.65 [169mm] | 138.14 LBS |
| HB16-D8S38DP | 2500 LBS | 4.88 [124mm] | 7.77 [198mm] | 150.39 LBS |

- NOTES:
- MAXIMUM RATED CAPACITY :
 - MAY EXCEED CAPACITY OF THE ROPE.
 - USE ROPE MANUFACTURER'S RATING AND SAFETY FACTOR TO DETERMINE LOAD LIMIT.
 - WHEN PROPERLY INSTALLED, MAINTAINED AND OPERATED.
 - IS BASED ON CABLES WRAPPED 90 DEGREES AROUND THE SHEAVE.
 - MOUNTING HARDWARE MUST BE DISTRIBUTED EVENLY.
 - MINIMUM OF 4 ATTACHMENT POINTS.
 - CONTACT FACTORY FOR NON-STANDARD REQUIREMENTS.

H - HEAD
 B - BLOCK
 # - SHEAVE DIAMETER
 -
 D - UNDERHUNG MOUNTING
 # - NUMBER OF GROOVES
 N - SHEAVE MATERIAL (N=NYLATRON, S=STEEL)
 # - ROPE SIZE (LIFT LINE)
 D - DOUBLE
 P - PURCHASE

| ZONE | REV | AUTHOR | DATE | DESCRIPTION |
|------|-----|------------|----------------|-------------|
| A | JCA | 11/02/2021 | SEE ECN #15023 | |

DRAWINGS FOR PRODUCTION APPROVAL. MANUFACTURE WILL NOT BEGIN UNTIL APPROVED DRAWING IS RETURNED TO THERN INC.

COMPANY NAME _____
 PRINT NAME _____
 SIGNATURE _____ DATE _____

THIS PRINT AND THE INFORMATION HEREIN IS THE PROPERTY OF THERN INC AND MUST NOT BE REPRODUCED EITHER IN FULL OR IN PART WITHOUT WRITTEN APPROVAL BY THERN INC.

16" HEAD BLOCK UNDER DP

SCALE: 1/2

DATE: 11/5/2015

DRAWN BY: JCA

DESCRIPTION: DIMENSIONAL DRAWING

REV: D

REVISED BY: A

REVISED DATE: 11/5/2015

REVISED DESCRIPTION: D4553

THERN Winches & Cranes

5712 INDUSTRIAL PARK ROAD
 WINONA, MN 55987
 PHONE 1-507-454-2996
 WWW.THERN.COM